

SAFETY DATA SHEET

Chartek 1709 PART A

Section 1. Identification

Chartek 1709 PART A HCA179

: GHS product identifier

: Product code

Identified uses	
Professional application of coatings and inks	
Uses advised against	Reason
All Other Uses	
AkzoNobel Saudi Arabia Ltd. PO Box 37 Dammam 31411 Saudi Arabia	: Supplier's details
Tel: +966 3 812 1044 Fax: +966 3 812 1169	
+966 3 812 1044	: Emergency telephone number (with hours of operation)
+966 55 388 0087	: <u>National advisory body/</u> <u>Poison Centre (For use only</u> <u>by licensed medical</u> <u>professionals.)</u>
sdsfellinguk@akzonobel.com	: e-mail address of person responsible for this SDS
Section 2. Hazards identification	
SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 LONG-TERM AQUATIC HAZARD - Category 2	: Classification of the substance or mixture
GHS label elements	: Hazard pictograms
Warning	: Signal word
Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.	: Hazard statements
Precautionary statements Wear protective gloves. Wear eye or face protection. Avoid release to th environment. Avoid breathing dust. Wash hands thoroughly after handlin Contaminated work clothing should not be allowed out of the workplace.	

AkzoNobel

X.International

Section 2. Hazards identificationCollect spillage. IF ON SKIN: Wash with plenty of soap and water. Take off
contaminated clothing and wash it before reuse. If skin irritation or rash occurs:
Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation
persists: Get medical attention.: ResponseNot applicable.: StorageDispose of contents and container in accordance with all local, regional, national
and international regulations.: DisposalWear appropriate respirator when ventilation is inadequate.: Supplemental label
elements

None known.

Section 3. Composition/information on ingredients

Mixture

: Substance/mixture

: Other hazards which do not result in classification

Classification	CAS number	% by weight	Ingredient name
Skin Irrit. 2, H315	25068-38-6	≥25 - ≤50	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin
Eye Irrit. 2A, H319			
Skin Sens. 1, H317			
Aquatic Chronic 2, H411			
Aquatic Chronic 1, H410	115-86-6	≤10	triphenyl phosphate
Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317	15625-89-5	≤5	2,2-bis(acryloyloxymethyl)butyl acrylate

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures Immediately flush eyes with plenty of water, occasionally lifting the upper and lower : Eye contact eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. : Inhalation If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. : Skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear

Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

AkzoNobel

X.International.

Section 4. First aid measures		
Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	:	Ingestion
Most important symptoms/effects, acute and delayed		
Potential acute health effects		
Causes serious eye irritation.	:	Eye contact
Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.	:	Inhalation
Causes skin irritation. May cause an allergic skin reaction.	:	Skin contact
Irritating to mouth, throat and stomach.	:	Ingestion
Over-exposure signs/symptoms		
Adverse symptoms may include the following: pain or irritation watering redness	:	Eye contact
No specific data.	:	Inhalation
Adverse symptoms may include the following: irritation redness	:	Skin contact
No specific data.	:	Ingestion
Indication of immediate medical attention and special treatment needed, if nece) SS	sary
In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	:	Notes to physician
No specific treatment.	:	Specific treatments
No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear	:	Protection of first-aiders

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

None known.

gloves.

- This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- : Suitable extinguishing media
- : Unsuitable extinguishing media
- : Specific hazards arising from the chemical





Section 5. Firefighting measures

Section 5. Firenghung measures	
Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides	: Hazardous thermal decomposition products
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	: Special protective actions for fire-fighters
Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	: Special protective equipment for fire-fighters
Section 6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	
No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	: For non-emergency personnel
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	: For emergency responders
Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	: Environmental precautions
Methods and material for containment and cleaning up	
Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.	: Small spill
Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	: Large spill

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: 31/03/2017

4/11

: Protective measures

: Advice on general occupational hygiene



Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

: Conditions for safe storage, including any incompatibilities

XInternational

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Exposure limits	Ingredient name	
ACGIH TLV (United States, 3/2015). TWA: 3 mg/m ³ 8 hours.	triphenyl phosphate	
Good general ventilation should be sufficient to contaminants.	o control worker exposure to airborne	: Appropriate engineering controls
Emissions from ventilation or work process eq they comply with the requirements of environn cases, fume scrubbers, filters or engineering r equipment will be necessary to reduce emissio	nental protection legislation. In some nodifications to the process	: Environmental exposure controls
Individual protection measures		
Wash hands, forearms and face thoroughly af eating, smoking and using the lavatory and at Appropriate techniques should be used to rem Contaminated work clothing should not be allo contaminated clothing before reusing. Ensure showers are close to the workstation location.	the end of the working period. ove potentially contaminated clothing. wed out of the workplace. Wash	: Hygiene measures
Safety eyewear complying with an approved so assessment indicates this is necessary to avo gases or dusts. If contact is possible, the follo unless the assessment indicates a higher deg goggles.	d exposure to liquid splashes, mists, wing protection should be worn,	: Eye/face protection
Skin protection	Standard EN 274. Dratastive slaves	. Hend protoction
Use chemical resistant gloves classified under against chemicals and micro-organisms. Rec When prolonged or frequently repeated contac class of 6 (breakthrough time greater than 480 recommended. When only brief contact is exp of 2 or higher (breakthrough time greater than recommended. The user must check that the for handling this product is the most appropria particular conditions of use, as included in the The selection of a specific glove for a particular workplace should also take into account all rel not limited to: Other chemicals which may be I puncture protection, dexterity, thermal protecti materials, as well as the instructions/specifical Barrier creams may help to protect the expose applied once exposure has occurred.	commended: Viton® or Nitrile gloves. ct may occur, a glove with a protection o minutes according to EN 374) is ected, a glove with a protection class 30 minutes according to EN 374) is final choice of type of glove selected te and takes into account the user's risk assessment. NOTICE: ar application and duration of use in a evant workplace factors such as, but handled, physical requirements (cut/ on), potential body reactions to glove ions provided by the glove supplier.	: Hand protection
Personal protective equipment for the body sh being performed and the risks involved and sh before handling this product.		: Body protection

AkzoNobel

Section 8. Exposure controls/personal protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

: Other skin protection

XInternational

: Respiratory protection

Section 9. Physical and chemical properties

: Physical state : Colour	A
: Colour	<u>Appearance</u>
	Solid.
	Grey.
: Odour	Odourless.
: Odour threshold	Not available.
: pH	Not applicable.
: Melting point	Not available.
: Boiling point	Not available.
: Flash point	Closed cup: 101°C (213.8°F)
: Evaporation rate	Not available.
: Flammability (solid, gas)	Not available.
: Lower and upper explosive (flammable) limits	Not available.
: Vapour pressure	Not available.
: Vapour density	Not available.
: Relative density	1.42
: Solubility	Insoluble in the following materials: cold water.
: Partition coefficient: n- octanol/water	Not available.
: Auto-ignition temperature	Not available.
: Decomposition temperature	Not available.
: Viscosity	Kinematic (room temperature): 2000 mm ² /s (2000 cSt)
	Section 10. Stability and reactivity
redients. : Reactivity	No specific test data related to reactivity available for this product or its ingredients.
: Chemical stability	The product is stable.
occur. : Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
: Conditions to avoid	No specific data.
: Incompatible materials	No specific data.
: Solubility : Partition coefficient: n- octanol/water : Auto-ignition temperatu : Decomposition tempera : Viscosity gredients. : Reactivity : Chemical stability occur. : Possibility of hazardous	Insoluble in the following materials: cold water. Not available. Not available. Kinematic (room temperature): 2000 mm²/s (2000 cSt) Section 10. Stability and reactivity No specific test data related to reactivity available for this product or its ingredients. The product is stable.

Under normal conditions of storage and use, hazardous decomposition products : Hazardous decomposition products products



Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Exposure	Dose	Species	Result	Product/ingredient name
-	>7900 mg/kg	Rabbit	LD50 Dermal	triphenyl phosphate
-	3500 mg/kg	Rat	LD50 Oral	
-	5170 mg/kg	Rabbit	LD50 Dermal	2,2-bis(acryloyloxymethyl) butyl acrylate

Irritation/Corrosion

Observation	Exposure	Score	Species	Result	Product/ingredient name
-	100 milligrams	-	Rabbit	Eyes - Mild irritant	reaction product: bisphenol- A-(epichlorhydrin); epoxy resin
-	24 hours 20 milligrams	-	Rabbit	Eyes - Moderate irritant	
-	24 hours 5 milligrams	-	Rabbit	Eyes - Severe irritant	
-	24 hours 500 microliters	-	Rabbit	Skin - Moderate irritant	
-	24 hours 2 milligrams	-	Rabbit	Skin - Severe irritant	
-	100 milligrams	-	Rabbit	Eyes - Moderate irritant	2,2-bis(acryloyloxymethyl) butyl acrylate
-	24 hours 500 milligrams	-	Rabbit	Skin - Moderate irritant	

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Not available.

Potential acute health effects

Causes serious eye irritation.

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Causes skin irritation. May cause an allergic skin reaction.

- : Information on likely routes of exposure
- : Eye contact
- : Inhalation
- : Skin contact



K.International.

Section 11. Toxicological information		
rritating to mouth, throat and stomach.	:	Ingestion
Symptoms related to the physical, chemical and toxicological characteristics		
Adverse symptoms may include the following: pain or irritation watering redness	:	Eye contact
No specific data.	:	Inhalation
Adverse symptoms may include the following: rritation redness	:	Skin contact
No specific data.	:	Ingestion
<u>Delayed and immediate effects as well as chronic effects from short and long</u>	-tern	<u>n exposure</u>
Short term exposure		
Not available.	:	Potential immediate effects
Not available.	:	Potential delayed effects
Long term exposure		
Not available.	:	Potential immediate effects
Not available.	:	Potential delayed effects
Potential chronic health effects		
Not available.		
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	:	General
	:	Carcinogenicity
No known significant effects or critical hazards.		
No known significant effects or critical hazards. No known significant effects or critical hazards.	:	Mutagenicity
-	:	Mutagenicity Teratogenicity
No known significant effects or critical hazards.	:	• •

Numerical measures of toxicity Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity			
Exposure	Species	Result	Product/ingredient name
96 hours	Algae - Pseudokirchneriella subcapitata	Acute EC50 2000 μg/l	triphenyl phosphate
96 hours	Fish - Oncorhynchus mykiss - Fingerling	Acute EC50 225 µg/l Fresh water	
48 hours	Daphnia - Daphnia magna	Acute LC50 1000 µg/l Fresh water	
30 days	Fish - Oncorhynchus mykiss - Fingerling	Chronic NOEC 55 µg/l Fresh water	

Persistence and degradability

Section 12. Ecological information

Biodegradability	Photolysis	Aquatic half-life	Product/ingredient name
Not readily	-		reaction product: bisphenol- A-(epichlorhydrin); epoxy resin

Bioaccumulative potential

Potential	BCF	LogPow	Product/ingredient name
low low low	- 190.546071796 -	2.64 to 3.78 4.63 0.67	reaction product: bisphenol- A-(epichlorhydrin); epoxy resin triphenyl phosphate 2,2-bis(acryloyloxymethyl) butyl acrylate

Mobility in soil

Not available.

coefficient (Koc)

No known significant effects or critical hazards.	
---	--

Section 13. Disposal considerations

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

ΙΑΤΑ	IMDG	UN	
UN3077	UN3077	UN3077	UN number
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, triphenyl phosphate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, triphenyl phosphate). Marine pollutant	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, triphenyl phosphate)	UN proper shipping name
9	9	9	Transport hazard class(es)
III			Packing group
Date of issue/Date of revision	: 31/03/2017		AkzoNobol

Date of issue/Date of revision Version : 3

XInternational

AkzoNobel

: Soil/water partition

: Other adverse effects

: Disposal methods

X.International.

Section 14. Transport information

Yes.	Yes.	Yes.	Environmental hazards
transported in sizes of ≤5 L or ≤5 kg, provided the	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	Additional information

Not applicable.

Not available.

: IMDG Code Segregation group

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Special precautions for user

: Transport in bulk according to Annex II of Marpol and the IBC Code

Section 15. Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients).

: Safety, health and environmental regulations specific for the product

Section 16. Other information

Justification

Justification	Classification		
Calculation method	Skin Irrit. 2, H315		
Calculation method	Eye Irrit. 2A, H319		
Calculation method	Skin Sens. 1, H317		
Calculation method	Aquatic Chronic 2, H411		

<u>History</u>

History		
31/03/2017	:	Date of printing
31/03/2017	:	Date of issue/Date of revision
02/06/2016	:	Date of previous issue
3	:	Version
ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations	:	Key to abbreviations
Not available.	:	References
Indicates information that has changed from previously issued version.		
Notice to reader		



 $\overline{}$

Section 16. Other information

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel

