

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM EPDM Tape Primer - SKUs 70005361, 70005362

Manufacturer or supplier's details

Company : Johns Manville
 Address : P.O. Box 5108
 Denver, CO USA 80127
 Telephone : +1 303-978-2000 8:00AM-5:00PM M-F
 Emergency telephone number : 1-800-424-9300 (Chemtrec, in English)

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2
 Skin irritation : Category 2
 Reproductive toxicity : Category 2
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
 Specific target organ toxicity - repeated exposure : Category 2
 Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

P210 Keep away from heat/sparks/open flames/hot surfaces.
 No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/
 equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/
 face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON
 CENTER/doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately
 all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air
 and keep comfortable for breathing. Call a POISON
 CENTER/doctor if you feel unwell.
 P308 + P313 IF exposed or concerned: Get medical advice/
 attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/
 attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or
 alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
Hazardous components

Chemical name	CAS-No.	Concentration (%)
heptane	142-82-5	>= 25 - <= 50
toluene	108-88-3	>= 25 - <= 50
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	>= 0 - <= 2.5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If unconscious place in recovery position and seek medical advice. Consult a physician after significant exposure.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If symptoms persist, call a physician.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Keep eye wide open while rinsing. If easy to do, remove contact lens, if worn. Protect unharmed eye. Seek medical advice.
If swallowed	: Gently wipe or rinse the inside of the mouth with water. Do not induce vomiting. If conscious, give 2 glasses of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	: None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Dry sand Dry chemical
Unsuitable extinguishing media	: Water
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Nitrogen oxides (NO _x) Bromine compounds
Further information	: Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment	: Wear self-contained breathing apparatus for firefighting if

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

for firefighters

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
heptane	142-82-5	TWA	85 ppm 350 mg/m ³	NIOSH REL
		C	440 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,000 mg/m ³	OSHA
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA
		CEIL	300 ppm	OSHA
		Peak	500 ppm (10 minutes)	OSHA

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Material : Nitrile rubber
- Material : Neoprene
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Eye protection : Tightly fitting safety goggles
Safety glasses with side-shields
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.
Keep away from food and drink.

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: colourless
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: not determined
Initial boiling point and boiling range	: 98 °C
Flash point	: -4 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7.0 %(V)
Lower explosion limit	: 1.1 %(V)
Vapour pressure	: 48 hPa (20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8090 g/cm ³
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 215 °C
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks. Direct sources of heat.
Incompatible materials	:	Oxidizing agents Acids Bases
Hazardous decomposition products	:	Carbon oxides Nitrogen oxides (NOx) Hydrocarbons Hydrogen bromide

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Components:****heptane:**

Acute oral toxicity	:	LD50 (Rat): > 15,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 103 mg/l Exposure time: 4 h
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg

Acute toxicity**toluene:**

Acute oral toxicity	:	LD50 Oral (Rat): 5,580 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 28.1 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit, male): > 5,000 mg/kg

Acute toxicity**Silane, dichlorodimethyl-, reaction products with silica:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0.45 mg/l Exposure time: 4 h Test atmosphere: dust/mist

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

Skin corrosion/irritation**Components:****heptane:**

Result: Skin irritation

Skin corrosion/irritation**toluene:**

Species: Rabbit

Result: Irritating to skin.

Skin corrosion/irritation**Silane, dichlorodimethyl-, reaction products with silica:**

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation**Components:****toluene:**

Species: Rabbit

Result: Mild eye irritation

Exposure time: 24 h

Serious eye damage/eye irritation**Silane, dichlorodimethyl-, reaction products with silica:**

Species: Rabbit

Result: No eye irritation

Germ cell mutagenicity**Components:****Silane, dichlorodimethyl-, reaction products with silica:**

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Result: negative

: Test Type: Ames test

Test species: Escherichia coli

Result: negative

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

Reproductive toxicity**Components:****toluene:**

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure**Components:****heptane:**

Assessment: May cause drowsiness or dizziness.

STOT - single exposure**toluene:**

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure**Components:****toluene:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Components:****heptane:**

Repeated dose toxicity - Assessment : Causes skin irritation.

Silane, dichlorodimethyl-, reaction products with silica:

Species: Rat

LOAEL: 0.031 mg/l

Application Route: Inhalation

Species: Rat

NOAEL: 500 mg/kg

Application Route: Oral

Aspiration toxicity**Components:****heptane:**

May be fatal if swallowed and enters airways.

toluene:

May be fatal if swallowed and enters airways.

Experience with human exposure**Components:****toluene:**

Skin contact:

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

Remarks: Prolonged skin contact may defat the skin and produce dermatitis.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****toluene:**Partition coefficient: n- : Pow: 2.7
octanol/water**Silane, dichlorodimethyl-, reaction products with silica:**Partition coefficient: n- : Remarks: Not applicable
octanol/water**Mobility in soil**

No data available

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological : No data available
information

SECTION 13. DISPOSAL CONSIDERATIONS

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

Disposal methods

Disposal of residual product : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION
International transport regulations

US DOT: UN1133, Adhesives, 3, II

SECTION 15. REGULATORY INFORMATION
TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D) : No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	2000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
 Acute Health Hazard
 Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene	108-88-3
---------	----------

Clean Air Act

JM EPDM Tape Primer

Version 1.0

Revision Date 01/10/2017

Print Date 05/24/2017

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

toluene	108-88-3	50 %
---------	----------	------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

toluene	108-88-3	50 %
---------	----------	------

Massachusetts Right To Know

toluene	108-88-3
heptane	142-82-5

Pennsylvania Right To Know

toluene	108-88-3
heptane	142-82-5

New Jersey Right To Know

toluene	108-88-3
heptane	142-82-5
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9

California Prop 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene	108-88-3
---------	----------

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 01/10/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.