# **Permatex**

# SAFETY DATA SHEET

Revision Date 24-Apr-2015 Version 1

# 1. IDENTIFICATION

**Product identifier** 

Product Name PERMA SHIELD GASKET DRESSING & FLANGE SEALANT 2 FL.OZ

Other means of identification

Product Code 85420 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address <u>Distributor</u>

ITW PermatexITW Permatex Canada10 Columbus Blvd.35 Brownridge Road, Unit 1Hartford, CT 06106 USAHalton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

# 2. HAZARDS IDENTIFICATION

#### Classification

# **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

#### Label elements

Emergency Overview		
Danger		

Causes serious eye irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Highly flammable liquid and vapor



Appearance Blue Physical state Liquid Odor Ketone

## **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

In case of inadequate ventilation wear respiratory protection

Contaminated work clothing should not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eve irritation persists: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

# **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Not applicable

Unknown acute toxicity

55.848% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
ACETONE	67-64-1	30 - 60	*
POLYESTER RESIN	9010-89-3	15 - 40	*
MODIFIED SILICON DIOXIDE	68611-44-9	5 - 10	*
DIPHENYLMETHANEDIISOCYANATE	101-68-8	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

#### Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition.

**Explosion data** 

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Use in well ventilated area. Use personal

protective equipment as required. Remove all sources of ignition.

**Environmental precautions** 

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

#### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents, Bases, Reducing agent, Amines

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
	(vacated) STEL: 2400 mg/m³ The		
	acetone STEL does not apply to the		
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	ļ
		(vacated) STEL: 1000 ppm	ļ

DIPHENYLMETHANEDIISOCYANA	TWA: 0.005 ppm	(vacated) Ceiling: 0.02 ppm	IDLH: 75 mg/m <sup>3</sup>
TE	• •	regulated under Methylene	Ceiling: 0.020 ppm 10 min
101-68-8		bisphenyl isocyanate	Ceiling: 0.2 mg/m <sup>3</sup> 10 min
		(vacated) Ceiling: 0.2 mg/m <sup>3</sup>	TWA: 0.005 ppm
		regulated under Methylene	TWA: 0.05 mg/m <sup>3</sup>
		bisphenyl isocyanate	_
		Ceiling: 0.02 ppm	
		Ceiling: 0.2 mg/m <sup>3</sup>	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Butyl acetate = 1

Air = 1

# Information on basic physical and chemical properties

Physical state Liquid
Appearance Blue
Odor Ketone

Odor threshold No information available

PropertyValuesRemarks • MethodpHNo information available

Melting point / freezing point

No information available

**Boiling point / boiling range**54 °C / 129 °F

Flash point
-18 °C / 0 °F

Evaporation rate < 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 12.8% Lower flammability limit: 2.6%

Vapor pressure Not determined

Vapor density >1

Relative density 1.04

Water solubility Partially soluble

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties

No information available

Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) <1%

DensityNo information availableBulk densityNo information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

# **Possibility of Hazardous Reactions**

None under normal processing.

#### Conditions to avoid

Heat, flames and sparks.

#### Incompatible materials

Strong oxidizing agents, Bases, Reducing agent, Amines

# **Hazardous Decomposition Products**

Carbon oxides Nitrogen oxides (NOx) Isocyanates

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

**Inhalation** May be harmful if inhaled. May cause sensitization by inhalation.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

**Skin contact** May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

**Ingestion** Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE	= 5800 mg/kg (Rat)	=	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
67-64-1			• , ,
DIPHENYLMETHANEDIISOCYANA	= 31600 mg/kg (Rat) = 9200	-	= 369 mg/m <sup>3</sup> (Rat) 4 h
TE	mg/kg(Rat)		, ,
101-68-8			

# Information on toxicological effects

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization Germ cell mutagenicity**No information available.
No information available.

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.Chemical NameACGIHIARCNTPOSHA

DIPHENYLMETHANEDIISO	-	Group 3	-	-
CYANATE		·		
101-68-8				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

# The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 6252 mg/kg ATEmix (dermal) 293922 mg/kg ATEmix (inhalation-dust/mist) 10.7 mg/l

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

59.3055% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ACETONE	-	4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96	magna mg/L EC50 Static 12600 -
		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	

#### Persistence and degradability

No information available.

# **Bioaccumulation**

No information available.

# Mobility

No information available.

Chemical Name	Partition coefficient
ACETONE	-0.24
67-64-1	

# Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal of wastes**This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

**Contaminated packaging** Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ACETONE	-	Included in waste stream:	-	U002
67-64-1		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ACETONE	Ignitable
67-64-1	

# 14. TRANSPORT INFORMATION

DOT

**UN/ID no** 1133

Proper shipping name: Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group || |
Emergency Response Guide 128

Number

<u>IATA</u>

**UN/ID no** ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9 ERG Code 9L

**IMDG** 

**UN/ID no** 1133

**Proper shipping name:** Adhesives, Limited Quantity (LQ)

Hazard Class 3
Packing Group II
EmS-No F-E, S-D

# 15. REGULATORY INFORMATION

**International Inventories** 

Complies **TSCA** Complies **DSL/NDSL EINECS/ELINCS** Not Listed. Not Listed. **ENCS IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND HOMOLOGUES] - 9016-87-9	1.0
[10M0E0G0E3] - 9010-87-9	

DIPHENYLMETHANEDIISOCYANATE - 101-68-8	1.0

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

# CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
DIPHENYLMETHANEDIISOCYANA	5000 lb	<del>-</del>	RQ 5000 lb final RQ
TE			RQ 2270 kg final RQ
101-68-8			

# **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
ETHANOL - 64-17-5	Carcinogen	
	Developmental	

# U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND HOMOLOGUES] 9016-87-9	Х	-	-
DIPHENYLMETHANEDIISOCYANA TE 101-68-8	Х	X	Х
ETHANOL 64-17-5	Х	X	Х
~DIPHENYLMETHANE-4,4 -DI-ISOCYANANTE ~ 2536-05-2	Х	-	-

# U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 2 Flammability 3 Instability 0

Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 24-Apr-2015

#### **Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**